



Note:

1.Material:

1.1 Insulator: P.B.T UL 94-V0 rated.

1.2 Contact: Brass,t=0.25mm.

1.3 Shell: Cold rolled steel,t=0.40mm.

2.Specification:

2.1 Current rating: 1 A Max.

2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.

2.3 Contact resistance: 30 mΩ Max.

2.4 Insulation resistance: 1000 MΩ Min at DC 500V.

2.5 Temperature range: -55°C~+105°C

3.Finishes:

3.1 Contacts:Gold flashed 1u",3u",5u",10U",15u",30u".

3.2 Shell:Nickel Plated.

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REWSEK	APPD

4	Down-shell	1	Cild rolled steel	T=0.40mm	Nickel Plated
3	Up-shell	1	Cild rolled steel	T=0.40mm	Nickel Plated
2	Contact	4	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Block
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO:	MATERIAL:	HSI-CHIN ELECTRONICS CO.,LTD			
MODEL NO:	FINSH:				
UNIT: mm	SIZE: A4	COLOR:	PART NAME:	IEEE 1394-6PIN(M) MOLDING	
TOLERANCE UNSPECIFIED		DR: 段林麗 '06/05/20	DWG NO:	S/A-343	REV: A0
.x ±0.3		CHK: Kevin '06/05/20	SCALE: 3:1	SHEET: 1 of 1	
.xxx ±0.20		APP: Kent '06/05/20			
ANG. ±1°					