




REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

- Note:
- 1.Material:
- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.20mm.
- 1.3 Shell: Cold rolled steel,t=0.40mm.

- 2.Specification:
- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total mating force: 5.0 Kgf Max.
- 2.6 Total unmating force: 2.5 Kgf Min.
- 2.7 Temperature range: -55°C~+105°C

- 3.Finishes:
- 3.1 contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel,tin or gold plated



PART NO	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	F±0.20	G±0.20
DIP-09S	30.80	25.00	16.30	7.90	16.80	12.60	2.77
DIP-15S	39.20	33.32	24.70	7.90	16.80	12.60	2.77
DIP-25S	53.05	47.04	38.40	7.90	16.80	12.60	2.77
DIP-37S	69.40	63.50	54.80	7.90	16.80	12.60	2.77

PART NO:	MATERIAL:		PART NAME:	
MODEL NO:	FINSH:		D-SUB P.C.B SOLDER(F)	
UNIT: mm	SIZE: A4	COLOR:		
TOLERANCE UNSPECIFIED		DR: 李霞		
.x ±0.3		06/04/21		
.xx ±0.20		06/04/21		
.xxx ±0.100		06/04/21		
AP:Kent	06/04/21	SCALE: 1:1	SHEET: 1 of 1	REV: A0