

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



Note:

1.Material:



- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Brass ,t=0.30mm.

2.Specification:

- 2.1 Rated voltage and current: 1.5A at 250V AC minimum.x.
  - 2.2 Dielectric withstanding voltage: 500V AC/1 minute without breakdown.
  - 2.3 Contact resistance:Before life test 30m ohm Max.  
After life test 50m ohm max.
  - 2.4 Insulation resistance: 1000M ohm Min at DC 500V.
  - 2.5 Insertion force: 35 Newtons Max.
  - 2.6 Extraction force: 10 Newtons Minmun.
  - 2.7 Solderability:Terminal shall be immersed in flux before text,  
Then dip in molten solder for 5±0.5 sec. At 245±5°C
- 3.Finishes:
- 3.1 Contacts:Gold flashed 1u ”,3u ”,5u ”,10U”,15u ”,30u ”.
  - 3.2 Shell: Nickel plated.



3	Shell	1	Brass	T=0.30mm	Nickel Plated
2	Contact	4	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/Ivory
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

PART NO:	MATERIAL:				
MODEL NO:	FINISH:				
UNIT: mm	SIZE: A4	COLOR:	PART NAME:		
TOLERANCE UNSPECIFIED		DR: 黃義強 '06/04/19			
.x	±0.3	CHK: Kevin '06/04/19		DWG NO: S/A-284-01	
.xx	±0.20	AP: Kent '06/04/19		REV: A1	
.xxx	±0.100	SCALE: 3:1		SHEET: 1 of 1	
ANG.	±1°	<div><div></div><div></div></div>			