



Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Insertion force: 4.5 Kgf Max.
6. Extraction force: 1.5 Kgf Min.
7. Temperature range: -55°C~+105°C

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

4	Hood	1	P.B.T	UL 94-V0	Black
3	Shell	1	Brass	T=0.40mm	80~120u"Nickel Plated
2	Contact	6	Brass	T=0.25mm	Contact area:0.8~1.2u"Gold Plated over 40u"Nickel min. Solder area:80~120u"Tin Plated over 40u"Nickel min.
1	Housing	1	P.B.T	UL 94-V0	Black
No. Name		Q'ty	Material	Remarks & Thickness	Finish
PART NO:			MATERIAL:		
MODEL NO:			FINSH:		
UNIT: mm		SIZE: A4	COLOR:		
TOLERANCE UNSPECIFIED			DR: 吳曉亮	06/11/06	
.x ±0.3			CHK: Kevin	06/11/06	
.xxx ±0.20			APP: Kent	06/11/06	
ANG. ±1					
			DWG NO:	IEEE 1394-6PIN (F) SOLDER(無折邊)	REV: A0
			SCALE:	3:1	SHEET: 1 of 1

HSI-CHIN ELECTRONICS CO.,LTD