



Note:

Specification:

1. Rated voltage and current: 1.5 A at 250V AC minimum.x.
2. Dielectric withstanding voltage: 500V AC/1 minute without breakdown.
3. Contact resistance:Before life test 30m ohm Max.
After life test 50m ohm max
4. Insulation resistance: 1000M ohm Min at DC 500V.
5. Insertion force: 35 Newtons Max.
6. Extraction force: 10 Newtons Minimum.
7. Solderability:Terminal shall be immersed in flux before text,
Then dip in molten solder for 5±0.5 sec. At 245±5°C

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

3	Shell	1	Brass	T=0.30mm	80~120u"Nickel Plated
2	Contact	4	Brass	T=0.25mm	Contact area:0.8~1.2u" Gold Plated over 40u"Nickel min. Solder area:80~120u" Tin Plated over 40u" Nickel min.
1	Housing	1	P.B.T	UL 94-V0	Black/Ivory
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

PART NO:			MATERIAL:		
MODEL NO:			FINSH:		
UNIT:	mm	SIZE: A4	COLOR:		
TOLERANCE UNSPECIFIED			DR: 吳曉亮 06/09/17		
.x	±0.3		USB-A(F) SOLDER-USB-A(F) SOLDER-1		
.xx	±0.20		CHK: Kevin 06/09/17		
.xxx	±0.100		AP: Kent 06/09/17		
ANG.	±1°		SCALE: 3:1		

HSI-CHIN ELECTRONICS CO.,LTD

PART NAME:

DWG NO:

S/A-284-02

REV: A1

