



Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 100 MΩ Min at DC 500V.
5. Temperature range: -40°C~+85°C
6. Insertion Force: 3.0Kgf Max.
7. Extraction Force: 0.4Kgf Min.

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

4	Earth terminal	1	Brass	T=0.40mm	Nickel Plated
3	Contact	1	Brass	T=0.25mm	Silver Plated
2	Housing	1	PA66+30%G	UL 94-V0	Yellow/White
1	Insulator	1	P.B.T	UL 94-V0	Yellow/White
No.	Part Name	Q'ty	Material	Remarks&Thickness	Finish/Color
PART NO:		MATERIAL:		<div> HSI-CHIN ELECTRONICS CO.,LTD</div>	
MODEL NO:		FINISH:			
UNIT: mm		COLOR:			
TOLERANCE UNSPECIFIED		COLOR:		PART NAME:	
.x	±0.3	DR:高朋祥 '07/02/02		PIN RCA JACK	
.xx	±0.20	CHK: Kevin '07/02/02		DWG NO:	
.xxx	±0.100	APP: Kent '07/02/02		SCALE: 3:1	
ANG.	±1°			SHEET: 1 of 1	
				REV: A0	
					

HSI-CHIN ELECTRONICS CO.,LTD

PIN RCA JACK

DR:高朋祥 '07/02/02

CHK: Kevin '07/02/02

APP: Kent '07/02/02

DWG NO:

SCALE: 3:1

SHEET: 1 of 1

REV: A0