



REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD
△			變更膠芯主體材質PA46→LCP	09/08/20	趙承寶	James

Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Temperature range: -55°C~+105°C

5	Shell	1	Stainless Steel	T=0.20mm	Nickel Plated
4	Spring	1	Stainless Steel	T=0.40mm	No Plated
3	Contact	5	Phosphor bronze	T=0.20mm	Contact area: 30u" Gold Plated over 40u" Nickel min. Solder area: 80~120u" Tin Plated over 40u" Nickel min.
2	Hood	1	LCP	UL 94-V0	Black
1	Housing	1	LCP	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PRAT NO:		MATERIAL:		HSI-CHIN ELECTRONICS CO.,LTD	
MODEL NO:		FINSH:			
UNIT: mm	SAZE: A4	COLOR:		PART NAME:	
TOLERANCE UNSPECIFIED		DR: 趙承寶 09/06/10		MICRO USB-5PIN(M)SOLDER(三條肋)	
.X ±0.30	.XX ±0.20	CHK: James 09/06/10		DWG NO: S/A-574	REV. A1
.XXX ±0.10	ANG ±1°	APP: Kent 09/06/10		SCALE: 1:1	SHEET: 1 of 1

ROHS Compliant