

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Note:

1.Material:




- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.60mm.
- 1.3 Shell: Brass,t=0.40mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total unmating force: 6.0 Kgf Max.
- 2.6 Total unmating force: 3.0 Kgf Min.
- 2.7 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 contacts:Gold flashed or Tin plated 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel plated or Gold plated



3	Shell	1	Brass	T=0.40mm	Nickel/Gold Plated
2	Contact	9	Brass	T=0.60mm	Gold Flashed/Tin Plated
1	Housing	1	P.B.T	UL 94-V0	Black/Green/Purple
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO:	MATERIAL:	HSI-CHIN ELECTRONICS CO.,LTD
MODEL NO:	FINSH:	

UNIT: mm	SIZE: A4	COLOR:	PART NAME:
TOLERANCE UNSPECIFIED			MINI DIN SOLDER 9PIN TYPE(M)

DR: 吳曉亮 06/07/14	DWG NO:	S/A-260	REV: A0
CHK: Kevin 06/07/14	SCALE: 2:1	SHEET: 1 of 1	
APP: Kent 06/07/14			

