

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

*Notes:*

*1.Material:*



- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass, t=0.25mm.
- 1.3 Shell: Cold rolled steel, t=0.30mm.

*2.Specification:*

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

*3.Finishes:*

- 3.1 Contacts:Gold flashed 1u",3u",5u",10u",15u",30u".
- 3.2 Shell: Nickel,tin plated



No.	Part Name	Q'ty	Material	Remarks&Thickness	Finish
3	Shell	1	Cold Rolled Steel	T=0.30mm	Nickel Plated
2	Contact	4	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/White

PART NO:		MATERIAL:			
MODEL NO:		FINISH:			
UNIT: mm	SIZE:A4	COLOR:		PART NAME: USB-A公焊線式短鐵殼	
TOLERANCE UNSPECIFIED		DR: 黃義強 06/04/05		DWG NO: S/A-275	
X ±0.30	.xx ±0.20	CHK: Kevin 06/04/05		SCALE: 3:1	
.xxx ±0.10	±0.10	APP: Kent 06/04/05		SHEET: 1 of 1	
ANG. ±1				REV: A0	