



REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Temperature range: -55°C~+105°C

3	Shell	1	SPCC	T=0.30mm	Cu:40"min.80u"~120u"Nickel Plated
2	Contact	9	Brass	T=0.25mm	Contact area:0.8~1.2u" Gold Plated over 40u"Nickel min. Solder area:80~120u" Tin Plated over 40u" Nickel min.
1	Housing	1	PA9T	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PRAT NO:		MATERIAL:			
MODEL NO:		FINSH:			
UNIT: mm	SAZE: A4	COLOR:		PART NAME:	
TOLERANCE UNSPECIFIED		DR: 趙承寶 09/07/13		USB-A(M)SMT(沉板式) 3.0版	
.X ±0.30	.XX ±0.20	CHK: James 09/07/13		DWG NO:	
.XXX ±0.10	ANG ±1°	APP: Kent 09/07/13		REV. A0	
				SCALE: 1:1	SHEET: 1 of 1

ROHS Compliant