



REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Note:

- Specification:
1. Current rating: 1 A Max.
 2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
 3. Contact resistance: 30 mΩ Max.
 4. Insulation resistance: 100 MΩ Min at DC 500V.
 5. Temperature range: -55°C~+105°C

No.	Name	Q'ty	Material	Remarks & Thickness	Finish
7	Top Shell	1	SPCC	T=0.30mm	Cu:40"min.80u"~120u"Nickel Plated
6	Down Shell	1	SPCC	T=0.30mm	Cu:40"min.80u"~120u"Nickel Plated
5	Shell	1	SUS	T=0.20mm	Nickel Plated
4	Spring	1	SUS	T=0.40mm	Nickel Plated
3	Contact	10	Phosphor bronze	T=0.20mm	Contact area:15u"Gold Plated over 40u"Nickel min. Solder area:80~120u"Tin Plated over 40u"Nickel min.
2	Hood	1	LCP	UL 94-V0	Black
1	Housing	1	PA66	UL 94-V0	Black

PRAT NO:		MATERIAL:			
MODEL NO:		FINSH:			
UNIT: mm	SAZE: A4	COLOR:		PART NAME:	
TOLERANCE UNSPECIFIED		DR: 劉新洪 10/06/08		MICRO USB-B TYPE(M)SOLDER(3.0版)	
.X ±0.20	.XX ±0.10	CHK: James 10/06/08		DWG NO: S/A-590	REV. A0
.XXX ±0.05	ANG ±1°	APP: Kent 10/06/08		SCALE: 1:1	SHEET: 1 of 1

