



REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 30V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Insertion force: 35 Newtons Max.
6. Extraction force: 10 Newtons Min.
7. Temperature range: -30°C~+80°C

3	Shell	1	Brass/SUS304	T=0.25mm	Nickel Plated
2	Contact	5	Brass	T=0.15mm	Contact area:0.8~1.2u"Gold Plated over 40u"Nickel min. Solder area:80~120u"Tin Plated over 40u"Nickel min. (ALL Gold)
1	Housing	1	LCP	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PRAT NO:		MATERIAL:			
MODEL NO:		FINSH:			
UNIT: mm	SAZE: A4	COLOR:	PART NAME: MICRO USB 5F SMT		
TOLERANCE UNSPECIFIED		DR: 鄭偉 '18/07/27		DWG NO: S/A-00012	
.X ±0.30	.XX ±0.20	CHK:楊育成 '18/07/27		REV: A0	
.XXX ±0.10	ANG ±1	APP:Kent '18/07/27		SCALE: SHEET: 1 of 1	

ROHS Compliant